

IN THE CLAIMS

Amendments to the Claims:

Please amend Claim 1.

This listing of claims will replace all prior versions, and listing of claims in the application.

Listing of Claims:

Claim 1 (currently amended): Method of determining the velocity v and anellipticity η parameters for processing seismic traces obtained from seismic receivers in a common midpoint (CMP) gather including an anelliptic NMO correction, comprising:

- a preliminary step to define a plurality of nodes (dtn, τ_0) , the said nodes being indicative of parameters dtn and τ_0 representing the NMO correction for the maximum offset and the zero offset travel time in hyperbolic coordinates, the said preliminary step being followed by
 - for each node (dtn, τ_0) defined in the preliminary step, the following steps:
 - for static NMO correction of traces in the CMP gather as a function of the values of the said parameters dtn, τ_0 at the node considered, and
 - for calculating the semblance function associated with the said NMO correction for the node considered; and
 - for each picked time t_0 , a step including determination of the maximum semblance node $(dtn(t_0), \tau_0(t_0))$,
 - a step to convert the $dtn(t_0)$ and $\tau_0(t_0)$ parameters so as to obtain the velocity $V(t_0)$ and anellepticity $\eta(t_0)$ laws
 - and a step of processing the seismic traces in view of the velocity $V(t_0)$ and anellepticity $\eta(t_0)$ laws.

Claim 2 (original): Method according to claim 1, wherein the nodes are defined during the preliminary step in an analysis volume (dt_n , τ_o , t_o) determined by minimum and maximum values respectively $[dt_{n\min}, dt_{n\max}]$, $[\tau_{o\min}, \tau_{o\max}]$ and $[t_{o\min}, t_{o\max}]$ of the dt_n , τ_o , and t_o parameters.

Claim 3 (original): Method according to claim 2, wherein, during the preliminary step, a corridor $[dt_{n\min}(t_o), dt_{n\max}(t_o)]$, $[\tau_{o\max}(t_o), \tau_{o\min}(t_o)]$ for max changing dt_n and τ_o parameters is delimited inside the analysis volume as a function of plausible velocity V and anellipticity η values, the nodes (dt_n , τ_o) defined for applying the NMO correction being then located along the corridor thus delimited.

Claim 4 (previously presented): Method according to claim 1, further comprising, for each node (dt_n , τ_o), a stacking step of the corrected seismic traces, following the semblance function calculation step.

Claim 5 (original): Method according to claim 4, wherein the stacking of corrected traces is done using only near offset traces.

Claim 6 (previously presented): Method according to claim 4, further comprising for each picked time, and following the step for determining the maximum semblance node, a step of checking that values dt_n and τ_o of the maximum semblance node correspond to a stacking extreme value for the same values dt_n and τ_o .

Claim 7 (previously presented): Method according to claim 1, further comprising a step of selecting and adjusting the pickings obtained, following the step implemented for determining the maximum semblance node ($d_{tn}(t_0)$, $\tau_0(t_0)$) for each picked time t_0 , before the conversion step.

Claim 8 (original): Method according to claim 7, wherein the said step of selecting and adjusting the pickings comprises a step of only retaining pickings d_{tn} and τ_0 for which time to the highest semblance pickings is greater than a predefined value.

Claim 9 (original): Method according to claim 8, wherein the said step of selecting and adjusting the pickings also comprises a step for adjusting the retained pickings d_{tn} and τ_0 by parabolic interpolations using values about the said picked values.

Claim 10 (original): Method according to claim 9, wherein the said step of selecting and adjusting pickings also comprises a step of eliminating retained and adjusted pickings d_{tn} and τ_0 when it is impossible to calculate the Dix interval velocities between the picking considered and higher semblance pickings.

Claim 11 (previously presented): Method according to claim 1, wherein the processing applied to seismic traces is an NMO correction process implementing a static correction $CORR_{NMO}$.

Claim 12 (original): Method according to claim 11, wherein, during the preliminary step, the NMO corrections $CORR_{NMO}$ are calculated for all nodes (dtn, τ_0) including in the analysis volume and all offsets of processed seismic traces.

Claim 13 (original): Method according to claim 12, wherein the NMO correction carried out for each node (dtn, τ_0) , consists of applying NMO corrections $CORR_{NMO}$ calculated during the preliminary step.

Claim 14 (previously presented): Method according to claim 11, wherein for a given (dtn, τ_0) pair, the static NMO correction $CORR_{NMO}$ of a seismic trace with offset x is carried out according to the following equation:

$$CORR_{NMO}(x) = -\tau_0 + \sqrt{\tau_0^2 + \frac{dtn(dtn + 2\tau_0)}{x_{max}^2}} x^2$$
 in which X_{max} represents the maximum offset in the CMP gather.

Claim 15-19 (withdrawn)

Claim 20 (previously presented): Method according to claim 14, wherein, during the final conversion step, the parameters $dt_n(t_o)$, and (τ_o) are converted to the velocity law $v(t_o)$ according to the following equation:

$$V = \frac{x_{\max}}{\sqrt{dt_n(dt_n + 2\tau_o) \frac{t_o}{\tau_o}}}$$

Claim 21 (previously presented): Method according to claim 14, wherein, during the final conversion step, the parameter $\tau_o(t_o)$ is converted to the anellepticity $\eta(t_o)$ law according to

$$\eta = \frac{1}{8} \left(\frac{t_o}{\tau_o} - 1 \right)$$

Claim 22 (previously amended): Method according to claim 20, wherein parameter dt_n is defined with respect to the velocity v and anellepticity η according to the following equation:

$$dt_n = \frac{8\eta}{1+8\eta} t_o + \sqrt{\left(\frac{t_o}{1+8\eta} \right)^2 + \frac{x_{\max}^2}{(1+8\eta)^2}}$$

Claim 23 (original): Method according to claim 21, wherein parameter τ_o is defined according to anellepticity η according to the following equation:

$$\tau_o = \frac{t_o}{1+8\eta}$$

Claim 24 (withdrawn)

Claim 25 (original): Method according to claim 2, further comprising, for each node (dtn, τ_0) , a stacking step of the corrected seismic traces, following the semblance function calculation step.

Claim 26 (original): Method according to claim 25, wherein the stacking of corrected traces is done using only near offset traces.

Claim 27 (original): Method according to claim 25, further comprising for each picked time, and following the step for determining the maximum semblance node, a step of checking that values dtn and τ_0 of the maximum semblance node correspond to a stacking extreme value for the same values dtn and τ_0 .

Claim 28 (original): Method according to claim 2, further comprising a step of selecting and adjusting the pickings obtained, following the step implemented for determining the maximum semblance node $(dtn(t_0), \tau_0(t_0))$ for each picked time τ_0 , before the conversion step.

Claim 29 (original): Method according to claim 28, wherein the said step of selecting and adjusting the pickings comprises a step of only retaining pickings dtn and τ_0 for which time to the highest semblance pickings is greater than a predefined value.

Claim 30 (original): Method according to claim 29, wherein the said step of selecting and adjusting the pickings also comprises a step for adjusting the retained pickings d_{tn} and τ_0 by parabolic interpolations using values about the said picked values.

Claim 31 (original): Method according to claim 30, wherein the said step of selecting and adjusting pickings also comprises a step of eliminating retained and adjusted pickings d_{tn} and τ_0 when it is impossible to calculate the Dix interval velocities between the picking considered and higher semblance pickings.

Claim 32 (original): Method according to claim 2, wherein the processing applied to seismic traces is an NMO correction process implementing a static correction $CORR_{NMO}$.

Claim 33 (original): Method according to claim 32, wherein, during the preliminary step, the NMO corrections $CORR_{NMO}$ are calculated for all nodes (d_{tn} , τ_0) including in the analysis volume and all offsets of processed seismic traces.

Claim 34 (original): Method according to claim 32, wherein the NMO correction carried out for each node (d_{tn} , τ_0), consists of applying NMO corrections $CORR_{NMO}$ calculated during the preliminary step.

Claim 35 (original): Method according to claim 32, wherein for a given (dtn, τ_0) pair, the static NMO correction $CORR_{NMO}$ of a seismic trace with offset x is carried out according to the following equation:

$$CORR_{NMO}(x) = -\tau_0 + \sqrt{r_0^2 + \frac{dtn(dtn + 2r_0)}{x_{max}^2}} x^2 \text{ in which } X_{max} \text{ represents the maximum offset in the CMP gather.}$$

Claim 36-39 (withdrawn)

Claim 40 (currently amended): Method according to claim 36 2, wherein the processing applied to seismic traces is a PSTM migration using a static NMO correction $CORR_{PSTM}$, and

wherein, for a given pair (dtn and τ_0), the static NMO correction $CORR_{PSTM}$ is carried out according to the following equation:

$$CORR_{PSTM}(x) = -t_0 + \sqrt{\frac{\tau_0^2}{4} + \frac{dtn(dtn + 2\tau_0)(x - x_m + h)^2}{x_{max}^2}} + \sqrt{\frac{\tau_0^2}{4} + \frac{dtn(dtn + 2\tau_0)(x - x_m - h)^2}{x_{max}^2}}$$

where:

- x_m represents the coordinates of the midpoints,
- $x - x_m$ represents the migration aperture PSTM,
- h is the half source — receiver offset,
- x_{max} is the maximum offset and aperture of the migration.

Claim 41 (original): Method according to claim 35, wherein, during the final conversion step, the parameters $dtn(t_o)$ and (τ_o) are converted to the velocity law $v(t_o)$ according to the

following equation:
$$V = \frac{x_{\max}}{\sqrt{dtn(dtn + 2\tau_o) \frac{t_o}{\tau_o}}}$$

Claim 42 (original): Method according to claim 35, wherein, during the final conversion step, the parameter $\tau_o(t_o)$ is converted to the anellepticity $\pi(t_o)$ law according to

$$\eta = \frac{1}{8} \left(\frac{t_o}{\tau_o} - 1 \right)$$

Claim 43 (original): Method according to claim 41, wherein parameter dtn is defined with respect to the velocity v and anellepticity η according to the following equation:

$$dtn = \frac{8\eta}{1+8\eta} t_o + \sqrt{\left(\frac{t_o}{1+8\eta} \right)^2 + \frac{x_{\max}^2}{(1+8\eta)^2}}$$

Claim 44 (original): Method according to claim 42, wherein parameter τ_o is defined according to anellepticity η according to the following equation:

$$\tau_o = \frac{t_o}{1+8\eta}$$

Claim 45 (original): Method according to claim 3, further comprising, for each node (dt_n , τ_0), a stacking step of the corrected seismic traces, following the semblance function calculation step.

Claim 46 (original): Method according to claim 45, wherein the stacking of corrected traces is done using only near offset traces.

Claim 47 (original): Method according to claim 45, further comprising for each picked time, and following the step for determining the maximum semblance node, a step of checking that values dt_n and τ_0 of the maximum semblance node correspond to a stacking extreme value for the same values dt_n and τ_0 .

Claim 48 (original): Method according to claim 3, further comprising a step of selecting and adjusting the pickings obtained, following the step implemented for determining the maximum semblance node ($dt_n(t_o), \tau_0(t_o)$) for each picked time t_o , before the conversion step.

Claim 49 (original): Method according to claim 48, wherein the said step of selecting and adjusting the pickings comprises a step of only retaining pickings dt_n and τ_0 for which time to the highest semblance pickings is greater than a predefined value.

Claim 50 (original): Method according to claim 49, wherein the said step of selecting and adjusting the pickings also comprises a step for adjusting the retained pickings dt_n and τ_0 by parabolic interpolations using values about the said picked values.

Claim 51 (original): Method according to claim 50, wherein the said step of selecting and adjusting pickings also comprises a step of eliminating retained and adjusted pickings d_{tn} and τ_0 when it is impossible to calculate the Dix interval velocities between the picking considered and higher semblance pickings.